



RTG Series Pulse-Proof Chip Resistors Product Specification

| | |
|---------------|------------|
| Document No. | IE-SP-103 |
| Released Date | 2019/10/16 |
| Page No. | 1 |

1 Scope:

- 1.1 This specification is applicable to lead free and halogen free of RoHS directive for RTG series Pulse-Proof thick film chip resistors.
- 1.2 The product is for general electronic purpose.

2 Explanation Of Part Numbers: (EX)

| <div><div>RTG</div><div></div></div> | <div><div>0805</div><div></div></div> | <div><div>T</div><div></div></div> | <div><div>100</div><div></div></div> | <div><div>F</div><div></div></div> | |
|---------------------------------------|--|------------------------------------|--------------------------------------|--|----------------------|
| Type | Size | Packaging | Nominal Resistance | | Resistance Tolerance |
| Pulse-Proof Thick Film Chip Resistors | 0402 0603 0805 1206 2010 2512 | T : Taping | 4-Digit | E96Series EX. 10.2Ω=10R2 10KΩ=1002 | D=± 0.5% F=± 1% |

3 General Specifications:

| Type | Rate Power at 70℃ | Max. Working Voltage | Max. Overload Voltage | T.C.R. (ppm/℃) | Resistance Range | |
|-----------------------------|-------------------|----------------------|-----------------------|----------------|------------------|-------------|
| | | | | | D(±0.5%) E-96 | F(±1%) E-96 |
| RTG0402 | $\frac{1}{5}$ W | 50V | 100V | ±200 | 1Ω≤R≤10M | |
| RTG0603 | $\frac{1}{3}$ W | 75V | 150V | ±200 | 1Ω≤R≤10M | |
| RTG0805 | $\frac{1}{3}$ W | 150V | 300V | ±200 | 1Ω≤R≤150KΩ | |
| RTG1206 | $\frac{1}{2}$ W | 200V | 400V | ±200 | 1Ω≤R≤150KΩ | |
| RTG2010 | $\frac{3}{4}$ W | 200V | 400V | ±200 | 1Ω≤R≤150KΩ | |
| RTG2512 | 1W | 200V | 400V | ±200 | 1Ω≤R≤150KΩ | |
| Operating Temperature Range | | | | -55℃ ~ +155℃ | | |

| | | | | | |
|----------------|-------------|--------------|----------------|--|---|
| IE | | | QA | Remark | Issue Dep. DATA Center. Series No. 60 |
| Written 王荷花 | Checked | Approved | Signing 许国敏 | IT'S NOT UNDER CONTROL FOR PDF FILE PLS NOTE THE VERSION STATED.. | |
| | | | | Do not copy without permission | |




RTG Series Pulse-Proof Chip Resistors Product Specification

| | |
|---------------|------------|
| Document No. | IE-SP-103 |
| Released Date | 2019/10/16 |
| Page No. | 2 |

3.1 Power Derating Curve:

Operating Temperature Range : - 55 ~ 155 °C

For resistors operated in ambient temperatures above 70°C , power rating shall be derated in accordance with figure below .



3.2 Voltage Rating or Current Rating

Rated Voltage: The resistor shall have a DC continuous working voltage or a rms. AC continuous working voltage at commercial-line frequency and wave form corresponding to the power rating, as determined from the following:

$$E = \sqrt{R \times P}$$

E= Rated voltage (v)

P= Power rating (w)

R= Nominal resistance(Ω)

Remark

IT'S NOT UNDER CONTROL FOR PDF FILE
PLS NOTE THE VERSION STATED..

Do not copy without permission

Issue Dep. DATA Center.


Series No. **60**

3.3 Pulse Loading Capability

Single Pulse Load:


Pulse on a regular basis; maximum permissible peak pulse power (P_{max}) as a function of a pulse duration.

$$V_{peak} \leq 0402(100V) \cdot 0603(150V) \cdot 0805(300V) \cdot 1206(400V) \cdot 2010(400V) \cdot 2512(400V)$$



4 Dimensions:

Unit:mm



| Dimension | | L | W | H | L1 | L2 |
|-----------|-----------|-----------|-----------|--------------------|-----------|-----------|
| Type | Size Code | | | | | |
| RTG | 0402 | 1.00±0.10 | 0.50±0.05 | 0.30±0.05 | 0.20±0.10 | 0.25±0.10 |
| RTG | 0603 | 1.60±0.10 | 0.80±0.10 | 0.45±0.10 | 0.30±0.15 | 0.30±0.15 |
| RTG | 0805 | 2.00±0.10 | 1.25±0.10 | 0.50±0.10 | 0.35±0.20 | 0.35±0.15 |
| RTG | 1206 | 3.05±0.10 | 1.55±0.10 | 0.50±0.10 -0.05 | 0.45±0.20 | 0.35±0.15 |
| RTG | 2010 | 5.00±0.20 | 2.50±0.20 | 0.55±0.10 | 0.60±0.20 | 0.60±0.20 |
| RTG | 2512 | 6.30±0.20 | 3.20±0.20 | 0.55±0.10 | 0.60±0.20 | 0.60±0.20 |

Remark


IT'S NOT UNDER CONTROL FOR PDF FILE
PLS NOTE THE VERSION STATED..

Do not copy without permission

Issue Dep. DATA Center.

Series No. **60**

5 Structure Graph:



| | | | |
|---|------------------------|----|--------------------------|
| 1 | Ceramic substrate | 6 | 2nd Protective coating |
| 2 | Bottom inner electrode | 7 | Marking |
| 3 | Top inner electrode | 8 | Terminal inner electrode |
| 4 | Resistive layer | 9 | Ni plating |
| 5 | 1st Protective coating | 10 | Sn plating |

Remark

IT'S NOT UNDER CONTROL FOR PDF FILE
PLS NOTE THE VERSION STATED..

Do not copy without permission

Issue Dep. DATA Center.

Series No. **60**




RTG Series Pulse-Proof Chip Resistors Product Specification

| | |
|---------------|------------|
| Document No. | IE-SP-103 |
| Released Date | 2019/10/16 |
| Page No. | 5 |

6 Reliability Test:

6.1 Electrical Performance Test

| Item | Conditions | Specifications |
|---------------------------------------|---|---|
| | | Resistors |
| Temperature Coefficient of Resistance | $TCR \text{ (ppm/}^{\circ}\text{C)} = \frac{(R_2 - R_1)}{R_1 (T_2 - T_1)} \times 10^6$ R1: Resistance at room temperature R2: Resistance at -55°C or +125°C T1: Room temperature T2: Temperature -55°C or +125°C Refer to JIS-C5201-1 4.8 | Refer to item 3. general specifications |
| Short Time Overload | Applied 2.5 times rated voltage for 5 seconds and release the load for about 30 minutes, then measure its resistance variance rate. (Rated voltage refer to item 3. general specifications) Refer to JIS-C5201-1 4.13 | $\Delta R\% = \pm 0.5\%$ |
| Insulation Resistance | Put the resistor in the fixture, add 100 VDC in +, - terminal for 60 sec then measured the insulation resistance between electrodes and insulating enclosure or between electrodes and base material. Refer to JIS-C5201-1 4.6  | $\geq 10^9 \Omega$ |
| Dielectric Withstand Voltage | Put the resistor in the fixture, add VAC (see spec. below) in +, - terminal for. RTG0402、0603 apply 300 VAC 1 minute. RTG0805、1206、2010、2512 apply 500 VAC 1 minute. Refer to JIS-C5201-1 4.7 | No short or burned on the appearance. |
| Intermittent Overload | Put the tested resistor in chamber under temperature $25 \pm 2^{\circ}\text{C}$ and load the rated DC voltage for 1 sec on, 25 sec off, 10000^{+400}_0 test cycles, then it be left at no-load for 1 hour, then measure its resistance variance rate. Refer to JIS-C5201-1 4.13 | $\Delta R\% = \pm 1.0\%$ |
| ESD | Put the specimens on the test fixture and apply $\pm 3\text{KVDC}$ on terminals for 1sec. Afterwards, the specimens stabilize for 30min or more and measure of its resistance variance rate. Refer to EIAJED-4701-300 304 | $\Delta R\% = \pm 5.0\%$ |

Remark

IT'S NOT UNDER CONTROL FOR PDF FILE
PLS NOTE THE VERSION STATED..

Do not copy without permission

Issue Dep. DATA Center.

Series No. **60**



RTG Series Pulse-Proof Chip Resistors Product Specification

| | |
|---------------|------------|
| Document No. | IE-SP-103 |
| Released Date | 2019/10/16 |
| Page No. | 6 |

6.2 Mechanical Performance Test

| Item | Conditions | Specifications |
|------------------------------|--|--|
| | | Resistors |
| Terminal Strength | Test1:The resistor mounted on the board applied 5N pushing force on the sample rear for 10 sec. Test2:The resistor mounted on the board slowly add force on the sample rear until the sample termination is breakdown. Refer to JIS-C5201-1 4.16 | Test1:No evidence of mechanical damage. Test2: $\geq 5N$ |
| Resistance to Solvent | The tested resistor be immersed into isopropyl alcohol of 20~25°C for 5 minutes, then the resistor is left in the room for 48 hrs., and measured its resistance variance rate. Refer to JIS-C5201-1 4.29 | $\Delta R\% = \pm 0.5\%$ |
| Solderability | Preconditioning: Put the tested resistor in the apparatus of PCT, at a temperature of 105°C, humidity of 100% RH, and pressure of 1.22×10^5 Pa for a duration of 4 hours. Then after left the tested resistor in room temperature for 2 hours or more. Test method: The resistor be immersed into solder pot in temperature $235 \pm 5^\circ C$ for 2 ± 0.5 sec, then the resistor is left as placed under microscope to observe its solder area. Refer to JIS-C5201-1 4.17 | Solder coverage over 95% |
| Resistance to Soldering Heat | ◎Test method 1 (solder pot test): The tested resistor be immersed into molten solder of $260 \pm 5 / -0^\circ C$ for 10 +1/-0 seconds. Then the resistor is left in the room for 1 hour. ◎Test method 2 (solder pot test): The tested resistor be immersed into molten solder of $260 \pm 5 / -0^\circ C$ for 30+1/-0 seconds. Then the resistor is left as placed under microscope to observe its solder area. ◎Test method 3 (Electric iron test): Preheating temperature: $350 \pm 10^\circ C$ Electric iron preheating time : 3+1/-0 sec Preheating the electric iron on electrode termination, as after that step placed the iron over 60 min. and measured its resistance variance rate. Refer to JIS-C5201-1 4.18 | Test item 1: (1)Variance rate on resistance $\Delta R\% = \pm 0.5\%$ Test item 2: (1)Solder coverage over 95%. (2)The underlying material (such as ceramic) shall not be visible at the crest corner area of the electrode. Test item 3: (1)Variance rate on resistance $\Delta R\% = \pm 0.5\%$ |
| Joint Strength of Solder | ◎Bending Strength: Solder tested resistor on to PC board. Add force in the middle down, and under load measured its resistance variance rate. D:RTG02、03、05=5mm RTG1206=3mm RTG2010、2512=2mm Refer to JIS-C5201-1 4.33 | $\Delta R\% = \pm 1.0\%$ |

Remark

IT'S NOT UNDER CONTROL FOR PDF FILE
PLS NOTE THE VERSION STATED..

Do not copy without permission

Issue Dep. DATA Center.

Series No. **60**



RTG Series Pulse-Proof Chip Resistors Product Specification

| | |
|---------------|------------|
| Document No. | IE-SP-103 |
| Released Date | 2019/10/16 |
| Page No. | 7 |

6.3 Environmental Test

| Item | Conditions | Specifications | | | | | | | | |
|----------------------------|---|-------------------|--|--------------------|--------|---------------------|--------|----------------------------|-----------------|-----------|
| | | Resistors | | | | | | | | |
| Resistance to Dry Heat | Put tested resistor in chamber under temperature 155±5℃ for 1000 +48/-0 hours.Then leaving the tested resistor in room temperature for 60 minutes, and measure its resistance variance rate. Refer to JIS-C5201-1 4.25 | ΔR%=±1.0% | | | | | | | | |
| Thermal Shock | Put the tested resistor in the chamber under the Thermal Shock which shown in the following table shall be repeated 300 times consecutively. Then leaving the tested resistor in the room temperature for 1 hours, and measure its resistance variance rate. <table border="1"><thead><tr><th colspan="2">Testing Condition</th></tr></thead><tbody><tr><td>Lowest Temperature</td><td>-55±5℃</td></tr><tr><td>Highest Temperature</td><td>125±5℃</td></tr><tr><td>Temperature-retaining time</td><td>15 minutes each</td></tr></tbody></table> Refer to MIL-STD 202 Method 107 | Testing Condition | | Lowest Temperature | -55±5℃ | Highest Temperature | 125±5℃ | Temperature-retaining time | 15 minutes each | ΔR%=±1.0% |
| Testing Condition | | | | | | | | | | |
| Lowest Temperature | -55±5℃ | | | | | | | | | |
| Highest Temperature | 125±5℃ | | | | | | | | | |
| Temperature-retaining time | 15 minutes each | | | | | | | | | |
| Loading Life in Moisture | Put the tested resistor in the chamber under temperature 40±2℃, relative humidity 90~95% and load the rated voltage for 90 minutes on, 30 minutes off, total 1000 hours. Then leaving the tested resistor in room temperature for 60 minutes, and measure its resistance variance rate. Refer to JIS-C5201-1 4.24 | ΔR%=±1.0% | | | | | | | | |
| Load Life | Put the tested resistor in chamber under temperature 70±2℃ and load the rated voltage for 90 minutes on, 30 minutes off, total 1000 hours. Then leaving the tested resistor in room temperature for 60 minutes, and measure its resistance variance rate. Refer to JIS-C5201-1 4.25 | ΔR%=±1.0% | | | | | | | | |

Remark


IT'S NOT UNDER CONTROL FOR PDF FILE
PLS NOTE THE VERSION STATED..

Do not copy without permission

Issue Dep. DATA Center.

Series No. **60**

7 Measurement Point:

| Bottom electrode | | Unit : mm | |
|---|---------|-----------|-----------|
|  | DIM | A | B |
| | TYPE | | |
| | RTG0402 | 0.80±0.05 | 0.24±0.05 |
| | RTG0603 | 1.35±0.05 | 0.35±0.05 |
| | RTG0805 | 1.80±0.05 | 0.35±0.05 |
| | RTG1206 | 2.90±0.05 | 0.35±0.05 |
| | RTG2010 | 4.50±0.05 | 1.15±0.05 |
| | RTG2512 | 5.90±0.05 | 1.60±0.05 |

⊙ Current Terminal

⊖ Voltage Terminal

8 Plating Thickness:

8.1 Ni: $\geq 2\mu\text{m}$

8.2 Sn(Tin): $\geq 3\mu\text{m}$

8.3 Sn(Tin): Matte Sn

Remark

IT'S NOT UNDER CONTROL FOR PDF FILE
PLS NOTE THE VERSION STATED..

Do not copy without permission

Issue Dep. DATA Center.

Series No. **60**




RTG Series Pulse-Proof Chip Resistors Product Specification

| | |
|---------------|------------|
| Document No. | IE-SP-103 |
| Released Date | 2019/10/16 |
| Page No. | 9 |

9 Technical application notes: (This is for recommendation, please customer perform adjustment according to actual application)


9.1 Recommend Soldering Method:

9.1.1 Lead Free IR Reflow Soldering Profile



Remark: The peak temperature of soldering heat is $260 \pm 5/-0$ °C for 10 seconds

9.1.2 Lead Free Double-Wave Soldering Profile.(This applies to 0603 size inclusive above products)



9.1.3 Soldering Iron: temperature $350^{\circ}\text{C} \pm 10^{\circ}\text{C}$, dwell time shall be less than 3 sec.

Remark

IT'S NOT UNDER CONTROL FOR PDF FILE
PLS NOTE THE VERSION STATED..

Do not copy without permission

Issue Dep. DATA Center.

Series No. **60**




RTG Series Pulse-Proof Chip Resistors Product Specification

| | |
|---------------|------------|
| Document No. | IE-SP-103 |
| Released Date | 2019/10/16 |
| Page No. | 10 |

9.2 Recommend Land Pattern Design (For Reflow Soldering):

When a component is soldered, the resistance after soldering changes slightly depending on the size of the soldering area and the amount of soldering. When designing a circuit, it is necessary to consider the effect of a decrease or increase in its resistance.

Unit:mm



| DIM TYPE | A | B | C |
|-------------|-----|-----|-----|
| RTG0402 | 0.5 | 1.5 | 0.6 |
| RTG0603 | 0.8 | 2.1 | 0.9 |
| RTG0805 | 1.2 | 3.0 | 1.3 |
| RTG1206 | 2.2 | 4.2 | 1.6 |
| RTG2010 | 3.5 | 6.1 | 2.8 |
| RTG2512 | 3.8 | 8.0 | 3.5 |

9.3 Environment Precautions:

This specification product is for general electronic use, ABCO will not be responsible for any damage, cost or loss caused by using this specification product in any special environment. If other applications need to confirm with ABCO.

If consumer intends to use our Company product in special environment or condition (including but not limited to those mentioned below), then will need to make individual recognition of product features and reliability accordingly.

- Used in high temperature and humidity environment
- Exposed to sea breeze or other corrosive gas, such as Cl₂ 、H₂S 、NH₃ 、SO₂ and NO₂.
- Used in non-verified liquids including water, oil, chemical and organic solvents.
- Using non-verified resin or other coating material to seal or coat our Company product.
- After soldering, it is necessary to use water-soluble detergents to clean residual solder fluxes, even though no-clean fluxes are recommended.

9.4 Momentary Overload Precautions:

The product might be out of function when momentary overloaded. Please make sure to avoid momentary overloading while using and preserving.

Remark

IT'S NOT UNDER CONTROL FOR PDF FILE
PLS NOTE THE VERSION STATED..

Do not copy without permission

Issue Dep. DATA Center.

Series No. **60**



RTG Series Pulse-Proof Chip Resistors Product Specification

| | |
|---------------|------------|
| Document No. | IE-SP-103 |
| Released Date | 2019/10/16 |
| Page No. | 11 |



9.5 Operation and Processing Precautions:

- (a) Avoid damage to the edge of resistor and protective layer caused by mechanical stress.
- (b) Handle with care when printing circuit board (PCB) is divided or fixed on support body, because bending of printing circuit board (PCB) mounting will make mechanical stress for resistors.
- (c) Make sure the power rating is under the limit when using the resistor. When power rating is over the limit, the resistor will be overloaded. There might be machinery damage due to the climbing temperature.
- (d) If the resistor will be exposed under massive impact load (shock wave) in a short period of time, the working environment must be set up well before use.
- (e) Please make evaluation and confirmation when the product is well used in your company and have a through consideration of it's fail-safe design to ensure the system safety.

10 Storage and transportation requierment:

- 10.1 The temperature condition must be controlled at $25\pm5^{\circ}\text{C}$, the R.H. must be controlled at $60\pm15\%$. The stock can maintain quality level in two years.
- 10.2 Please avoid the mentioned harsh environment below when storing to ensure product performance and its' weldability. Places exposed to sea breeze or other corrosive gas, such as Cl_2 、 H_2S 、 NH_3 、 SO_2 and NO_2 .
- 10.3 When the product is moved and stored, please ensure the correct orientation of the box. Do not drop or squeeze the box. Otherwise, the electrode or the body of the product may be damaged.

11 The carton packaged for electronic-information products is made by the symbol as follows: (For china)

| | |
|---|--|
|  |  |
| Marking for control of pollution cause by electronic-information products | Marking for package recovery |

| | | |
|--------|--|------------------------|
| Remark | IT'S NOT UNDER CONTROL FOR PDF FILE PLS NOTE THE VERSION STATED.. | Issue Dep.DATA Center. |
| | Do not copy without permission | Series No. 60 |



RTG Series Pulse-Proof Chip Resistors Product Specification

| | |
|---------------|------------|
| Document No. | IE-SP-103 |
| Released Date | 2019/10/16 |
| Page No. | 12 |

Legal disclaimer

ABCO, its distributors and agents (collectively, "ABCO"), hereby disclaims any and all liabilities for any errors, inaccuracies or incompleteness contained in any product related information, including but not limited to product specifications, datasheets, pictures and/or graphics. ABCO may make changes, modifications and/or improvements to product related information at any time and without notice.

ABCO makes no representation, warranty, and/or guarantee about the fitness of its products for any particular purpose or the continuing production of any of its products. To the maximum extent permitted by law, ABCO disclaims (i) any and all liability arising out of the application or use of any ABCO product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for a particular purpose, non-infringement and merchantability.

ABCO defined this product is for general electrical use , not design for any application for automotive electrical ,life-saving or life support equipment, or any application which may inflict casualties if ABCO product failure occurred. When consumer is using or selling products of ABCO without having discussion with the sales representatives and specifically stated the applicability mentioned above in a written form, then the client need to take a full responsibility and agree to protect ABCO from punishment and damage.

Information provided here is intended to indicate product specifications only. ABCO reserves all the rights for revising this content without further notification, as long as products are unchanged. Any product change will be announced by ECN.

| | | |
|--------|--|-------------------------|
| Remark | IT'S NOT UNDER CONTROL FOR PDF FILE PLS NOTE THE VERSION STATED.. | Issue Dep. DATA Center. |
| | Do not copy without permission | Series No. 60 |